

GUILLOTINE **IDEAL 4850-95**

WITH AUTOMATIC CLAMP

475 mm cutting length | electro-mechanical blade and clamp drive | optical cutting line indicator with bright and durable LEDs | spindle guided backgauge with hand crank | measuring scale (mm/inches), located on front table | adjustable backgauge with narrow separations and plastic gliders | two side lays each on front and rear tables | high-quality blade made from "Solingen steel" | solid steel blade carrier and adjustable blade guides | automatic clamping system, guided on both sides for evenly distributed clamping pressure (clamp can be lowered or raised independently from blade) | solid all-metal construction | complete with stand and storage shelf | SCS (Safety Cutting System): hinged, electronically controlled safety guard on the front table; transparent safety cover on the rear table; main switch and safety lock with key; electronically controlled true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade and clamp return from every position; disc brake for instant blade stop; blade changing device with covered cutting edge; blade depth adjustment from the outside of the machine; easy blade change from the front of the machine without removing covers.

Power supply: 230 V / 50 Hz / 1~¹, Motor performance (input capacity): blade drive 1.1 kW, clamp drive 0.32 kW


Dimensions (H x W x D): 1230 x 755 x 970 mm, Weight: 209 kg, Colour: pearl grey.

¹ other voltages available



L.T.E. Listed 802 D

SAFETY GUARD



The electronically secured front safety guard swings out of the way easily and allows safe and convenient cutting.

PUSH BUTTON CONTROL



Push buttons allow, that the automatic clamp can be moved up and down independent of blade movement.

MEASURING SCALE



The precise measuring scale (mm/inches) for the backgauge positioning can be read easily and is located on the front table.

➔ IDEAL 4850-95

Cutting length	475 mm
Cutting height	80 mm
Narrow cut	30 mm
Table depth	458 mm
Power supply	230 V / 50 Hz ¹