

# DENMARK Laminator



The Denmark Laminator has been designed for the low to medium volume user who demands quality results and ease of use, combined with superior quality of both parts and design.

With simple controls and a user friendly design, even a first time user can quickly achieve professional results with little training. Perfect for protecting and enhancing awards, presentations, plans, teaching aids, maps, menus, signs, worksheets and more, the denmark is ideal for use in custom laminating businesses, government and council, offices and schools.

- 1650mm wide
- Variable speed (up to 4.6mts per minute)
- 2 Silicone rubber rollers (84mm diameter)
- Opens to 10mm (easy single lever action)
- Roller guard with built in safety sensor switch
- Upper and lower idle bar
- Complete with mobile stand and foot pedal
- Forward and reverse function
- Fits 76mm cores
- Lower mandrel with double ended brake.
- 2 emergency stop buttons

Model	CLMD 1650/Denmark Heat Assist Laminator
Top Roll Heat Assist	45/50c
Lam. Speed	Variable speed (up to 4.6mts per minute)
Lam. Width	1650 mm
Lam. Thickness	Opens up to 10mm
Power supply	AC 240 V / 50,60 Hz
Feed Tray Height	916mm
Assembled Dimensions	L1860 x D570 x H1300mm
Machine Shipping Dimension	L2000 x D490 x H590mm
Total Shipping Weight	189kg