

# Polypropylene CCP Cold Laminating Film

## PRODUCT INFORMATION

Construction:	CPP (Polypropylene)
Finish:	Matt
Thickness:	50 Microns.
Adhesive (Resin):	(P.S.A) - Pressure Sensitive Adhesive
Adhesive (Resin) Thickness:	24 Microns approx.
Total Thickness:	74 Microns approx.
Resin (Adhesive):	Clear Permanent Solvent Acrylic
Outdoor Life:	Yes
Shrinkage:	less than 0.1%

---

Cores:	All on 76mm
Roll Widths:	1300mm, 1520mm
Roll Lengths:	50 meters

---

L-180	1300mm x 50mtrs
L-181	1520mm x 50mts



Gray Laminating supplies

P: 0409 484 271

F: 07 3889 1401

[sales@graylaminating.com.au](mailto:sales@graylaminating.com.au)

## Technical Data: PVC Polymeric (P.S.A) Film

Test Items	Test Result	Standard	Test Method
Thickness, mm (without Paper and adhesive)	0.08-0.10	0.8-0.1	ASTM-D-1593
Tensile strength (kg/%)			
MD	240	220	
TD	230	200	
Elongation (%)			ASTM-D-882A
MD	200	180	
TD	180	180	
Tear Strength (kg/mm)			
MD	9.0	9.0	
TD	9.0	8.0	
Dimensional Stability (%)			10"x10" Sample
Shrinkage	0-0.5	0.2	adhere to aluminum